

Technical Specifications

Model Numbers	BM-i02		
Printing method	Direct thermal	Power supply	Input : AC 110V/240V 50~60 Hz Output : AC 9V-2A
Printing speed	80mm/s	Battery	2000m Ah
Paper width	58mm	Reliability	Printing head life: 50km
Paper roll diameter	≤30mm	Working environment	Temperature (0~45°C) humidity(10~80%)
Paper thickness	0.06~0.08mm	Storage environment	Temperature (-10~60°C) humidity(10~90%)
Resolution	8 dots (203dpi)	Drivers	Win9X/Win 2000/ Win 2003/Win XP/Win 7/ Win 8/Win 8.1/Linux / IOS/Android
Character size	ANK, Font A: 12x24 dots Font B: 9x17 dots simplified/traditional Chinese: 24x24 dots	Command	Compatible with ESC/POS
Column capacity	384 dots/line	Gross Weight	0.22kg(No paper roll)
Interface	Bluetooth+USB+Serial	Dimension	111x88x41mm (L x W x H)
Barcode	1D Barcode : UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODABAR / ITF / CODE39 / CODE93 / CODE128 2D Barcode : QR CODE / PDF417		
NV FLASH	64K Bytes		
Input buffer	32K Bytes		



Birch is a trademark of Birch Technology U.S.A. Inc
All other products, brands or companies are trademarks or registered
trademarks of their respective companies.

Specifications are subject to change without prior notice

Contact us for details