



IT606

IT606 Mobile terminal

5.5" Touch screen

Android 7.0 OS

The Right and Affordable Mobile Android Terminal to Grow Your Business

1. The e-Commerce is coming

It is obvious that the e-Commerce is getting more and more popular, and IT606 mobile Android terminal will be your good choice to solve your today's business challenges. IT606 mobile Android terminal offers the excellent mobile functions on ordering, recognitions, payment, printing....

2. Powerful platform

IT606 series mobile terminal with powerful platform as below:

- a. OS: Android 7.0
- b. CPU: Quad-core MT8735 series at 1.3Ghz, 64-bit
- c. Display: 5.5" IPS screen with P-CAP touch(Projected capacitive touch)
- d. Memory: 1GB RAM + 8GB ROM

3. My mobile terminal does it all for your business

- Built-in 2" (58mm) thermal pinter
- Built-in camera which is easily to identify the QR code.
- Supports GPS + AGPS
- Support WiFi(IEEE 802.11 a/b/g/n(2.4G/5G)
- Support microphone, speaker, headphone, TF card and Micro USB...



Ordering information :

IT606B: 5.5" Mobile Android terminal , P-CAP touch, MT8735 CPU, 1GB RAM, 8GB ROM



Technical Specifications

Model Numbers IT606

OS	Android 7.0
CPU	CPU at 1.3GHz , 64 bit quad-core processor
Memory	1GB RAM , 8GB ROM
Display	5.5 inches IPS , Resolution : 960 x 540 Pixels
Touch Screen	Capacitive multi-touch screen
Camera	5.0MP , Flash , AF
Speaker	1W
Headphones	3.5mm audio interface , stereo headphones supported
Microphone	MIC voice input
GPS + AGPS	Supported
Band	GSM : B2 / 3 / 5 / 8 WCDMA : B1 / 2 / 5 / 8 TD-SCDMA : B34 / 39 LTE-FDD : B1 / 3 / 7 / 20 LTE-TDD : B38 / 39 / 40 / 41
WIFI	IEEE 802.11 a / b / g / n (2.4G / 5G)
Bluetooth	Support Bluetooth 2.1 / 3.0 / 4.2 / Support BLE
Power button	Turn on / off (Press twice quickly to turn on the camera directly under locked screen)
Button	Power On Button(Volume Up / Volume Down)
SIM Card	Micro SIM card supported
TF Card	Capacity up to 32GB
MICRO USB	USB 2.0 OTG , can be charged by using the data cable(Set as permitted in the device) Developer debugging supported
Printing method	Thermal
Paper width	58mm
Paper roll diameter	40mm
Printing speed	70mm/s
Mechanism life	50km
Environment	Working temperature : 0°C ~ 50°C
Storage temperature	-20°C ~ 70°C
Battery	Non-removable lithium battery 6000mAh @ 3.8A
Adapter	INPUT : AC 100 ~ 240V / 1.5A OUTPUT : DC 5V / 2A
Size	205 x 86 x 54.5mm



Birch is a trademark of Birch Technology INC.
All other products, brands or companies are trademarks or registered trademarks of their respective companies.
Specifications are subject to change without prior notice

Contact us for details