

Technical Specifications

Top Case	Robust metal top case
Bottom case	Solid metal bottom case
Drawer	Heavy duty metal drawer with keylock
Font panel	Sturdy ABS plastic facia with Slip deposit Slot
Case tray	Heavy duty ABS plastic trays with 4 / 5 adjustable bill compartment, that fits all international currencies
Coin trays	Removable coin trays with 5 / 9 adjustable coin compartments complete coin tray may be removed separately from bill tray 4 / 5 adjustable bill tray
Solenoid release mechanism	12V / 2 PIN , or 24V / 6 PIN (12V / 6 PIN optional)
Drawer opener	Electromechanical or manual operation Pulse width : 100 to 200 milliseconds Pulse duty cycle : 10% MAX Peak current : Lampere
Dimensions	420 x 440 x 105mm (H) as standard 420 x 490 x 105mm (H) for optional for King size
Weight	Approx 10 Kgs

The Commands through RS-232 port :

Example 1 :	Under DOS	Mode COM 1: 9600
	Create a test file – TEXT.TXT-CONTENT="0", Copy TEST.TXT COM 1	
Example 2 :	Under QBASIC	Mode COM 1:9600
	Model LPT1-COM1	QBASIC
	10 for 1+1 to 10	10 LPRINT CHR\$(0)

PIN-ASSIGNMENTS or RS-232 serial connector

PIN#3 RX Received Data from host
PIN#5 GND ground
PIN#9 DC 12V serial connector board build a jumper-JPI
JPI OPEN-Use extend 12V DC adapter
JPI SHOT-Use DC 12V through RS-232 cable from host

PIN-ASSIGNMENTS 6-Pin 24V

PIN # 1	F.G.	FRNME GROUND
PIN # 2	L (-)	DR AWER KICK-OUT DRIVE SIGNAL
PIN # 3	NC	NC
PIN # 4	L (+)	+24VD FOR DRAWER KICK-UT SUPPLIED
PIN # 5	NC	NC
PIN # 6	NC	NC



บริษัท เทคโนโลยี สโตร์ จำกัด
TECHNOLOGY STORE CO.,LTD.

604/3 ศูนย์การค้าพันธุ์ทิพย์พลาซ่า ประตูน้ำ ชั้น M ห้อง M44,M1/1 ถนนเพชรบุรี แขวงถนนเพชรบุรี เขตราชเทวี กรุงเทพฯ 10400 โทร. 02-2506144-45 แฟกซ์ 02-2506146
604/3 Panthip Plaza Plaza Bldog Pratunm, 3rd Floor, Room M44, M1/1 Petchburi Rd., Rachtavee, Bangkok 10400 Tel.02-2506144-45 Fax.02-2506146

www.techno.co.th