


iF4

Standard thermal transfer desktop
barcode printer with 300-meter ribbon supported



- 152.4 mm/s (6") per second printing speed
- Mechanism structure design, easy for maintenance
- 1.1 GHz 32-bit RISC processor with 64 MB SDRAM
128 MB Flash memory
- USB, Ethernet interface as standard, optional Wi-Fi
or Bluetooth
- Free Seagull Windows driver and Bartender, and
iDPRT drivers and label design software
- ZPL II, DPL, TSPL emulation supported
- Various accessories include peeler, cutter, and
external paper stand
- Support Smart Printing Mode(TSPL)



Specification

Model	iF4	
Printing	Printing Method	Thermal Transfer
	Resolution	203 dpi/300 dpi
	Max. Printing Speed	6 ips (203 dpi), 5 ips (300 dpi)
	Max. Printing Width Max. Printing Length	108 mm (203 dpi)/108 mm (300 dpi) 1200 mm
CPU		32-bit RISC CPU
Memory	RAM	64 MB
	Flash	128 MB
Detection	Sensor	Out-of-paper detection, gap detection, ribbon detection, black mark detection, cover-opening detection
Media	Type	Continuous, Die-Cut, Black Mark, Fan-Fold, Notched (Outside Wound)
	Width	20 mm – 118 mm
	Thickness	60 µm – 200 µm
	O.D. I.D.	Max. 5 inches (127 mm) 0.5 inches (12.7 mm) , 1 inch (25.4 mm) , 1.5 inches(38 mm)
Ribbon	Type	Wax, Wax/Resin, Resin
	Width	40 mm –110 mm
	Length	Max. 984feet (300 m)
	Core Diameter	0.5/1 inch
Programming Language		ZPL II, TSPL, DPL
Software	Label Design Software	iDPRT BarTender Ultralite
	Driver	Windows 7,8,10, Server 2012/2016/2018, Seagull Driver
Resident Fonts	Bitmap Font	6, 8, 12, 16, 32, OCR A & B. 90°, 180°, 270° rotatable and 10 magnification.
	TTF Fonts	CG Triumvirate™times expandable in horizontal and vertical directions, simplified Chinese.
Codepage		DOS437,720,737,755,775,850,852,855,856,857,858,860,862,863,864,865, 866, Windows 1250,1251,1252,1253,1254, 1255,1256,1257,1258, ISO8859-1,-2,-3,-4,-5,-6,-8,-9,-15
Barcode	1D	Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11
	2D	PDF417, Maxicode, DataMatrix, QR Code, Aztec
Interface	Standard	USB, Ethernet
	Optional	Bluetooth 5.0/BLE,WiFi
User Interface		Two-color status light: standby, abnormal indication Feed, :Calibration Button:Calibrate
Power Supply		Power Switch Input: AC 100-240 V, 50/60 Hz Output: DC 24 V / 2 A
Environment	Operation	41°F(5°C) to 104°F(40°C) , humidity 30% to 85% ,non-condensing
	Storage	-4°F(-20°C) to 122°F(50°C), humidity 10% to 90% ,non-condensing
Physical Characteristic	Dimension(L*H*W)	282 mm×205 mm×168 mm (L×W×H)
	Weight	2.32 kg, excluding media
Options & Accessory		Peeler module, Guillotine cutter, external label roll holder,Rotary cutter
Agency Approval		CCC,CE,FCC,CB

iDPRT Xiamen Hanin Co.,Ltd.

ADD: 5F, 10# Building, Gaoqi South 12 Road, Aide Industrial Park, Huli District, Xiamen, P.R China

TEL: +86-(0)592-5932525 FAX: +86-(0)592-5885992

WEB: www.idprt.com EMAIL: info@idprt.com



iDPRT Official Website